


# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS


Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**

# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505




### SPECIFICATIONS

Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**


## MODEL M-505 SCHEMATIC DIAGRAM





# ONKYO® SERVICE MANUAL

## ULTIMATE STEREOPHONIC POWER AMPLIFIER Model M-505



### SPECIFICATIONS

Power Output	140 watts perchannel, min RMS, at 4 ohms both channels driven, from 20 Hz to 20 kHz, with no more than 0.05% total harmonic distortion. 105 watts perchannel, min, RMS, at 8 ohms both channels driven, from 20 Hz to 20kHz, with no more than 0.05% total harmonic distortion.	Power Output Dynamic	600 watts total at 4 ohms 0.05 % THD. 320 watts total at 8 ohms 0.05 % THD.
Total harmonic Distortion	0.05 % at Rated power 0.02 % at 1 watt output	Continuous	165 watts per channel, at 4 ohms, 1 kHz 0.05 % THD 110 watts per channel, at 8 ohms, 1 kHz 0.05 % THD
Intermodulation Distortion	0.01 % at Rated power	Power Supply Rating Controls	AC 120 V 60 Hz or AC 220 V 50 Hz POWER CUTOFF FREQUENCY SELECTOR (DC, 0.15 Hz, 10 Hz) Rear Panel LEVEL ADJUSTER (L, R) Rear Panel SPEAKERS
Gain	25.5 dB at 1 kHz	Outputs	INPUT Terminals
Frequency Response	+0, -1.5 dB at DC-150 kHz	Inputs	2 FETs, 45 Transistors, 31 Diodes
Input Sensitivity	1.5 V	Semiconductors	450 W (17-3/4" x 165 H (6-1/2") x 322 D (12 11/16"))
Input Impedance	100 k $\Omega$	Dimensions	17 kg. (37.4 lbs.)
Load Impedance	4-16 $\Omega$		
Damping Factor	100 (8 $\Omega$ , 1 kHz)		
Filter	0.15 Hz/10 Hz 6 dB/oct.		
Signal to Noise Ratio	110 dB (IHF A NETWORK)		

Specifications are subject to change without notice

**ONKYO®**  
**AUDIO COMPONENTS**